

INFORMACION TECNICA :: MOTORES TUBULARES

ADAPTADORES

GRAMPAS

MODELO	DIAMETRO TUBO [mm]	VOLTAJE [V]	FRECUENCIA [Hz]	POTENCIA [W]	CONSUMO [A]	VELOCIDAD [rpm]	TORQUE [Nm]	CARGA MAX. [kg]	TIEMPO MAX. FUNCIONAMIENTO	PROTECCION	LARGO TOTAL [mm]	MAX. DE GRIOS	CONTROL REMOTO	ASISTENCIA MANUAL	OCTO 40	RED 38	OCTO 60	OCTO 70	NERV 70	RED 80	OMEGA 10	OMEGA 14	L 10	L 14	CAJON 35	CAJON 45
TH 35-6	35	220	50	95	0,41	28	6	8	4	IP44	523	39			*	*					*		*		*	
TH 35-6/R	35	220	50	95	0,41	28	6	8	4	IP44	643	39	*		*	*					*		*		*	
TH 35-10	35	220	50	126	0,56	17	10	18	4	IP44	523	39			*	*					*		*		*	
TH 35-10/R	35	220	50	126	0,56	17	10	18	4	IP44	643	39	*		*	*					*		*		*	
TH 45-20	45	220	50	156	0,68	15	20	30	4	IP44	474	42					*	*			*		*		*	
TH 45-20/R	45	220	50	156	0,68	15	20	30	4	IP44	574	42	*				*	*	*		*		*		*	
TH 45-20/M	45	220	50	156	0,68	15	20	30	4	IP44	555	42		*			*	*	*		*		*		*	
TH 45-35	45	220	50	210	0,92	12	35	50	4	IP44	544	42					*	*	*		*		*		*	
TH 45-35/R	45	220	50	210	0,92	12	35	50	4	IP44	674	42	*				*	*	*		*		*		*	
TH 45-35/M	45	220	50	210	0,92	12	35	50	4	IP44	625	42		*			*	*	*		*		*		*	
TH 45-50	45	220	50	232	1,01	12	50	80	4	IP44	544	42					*	*	*		*		*		*	
TH 45-50/R	45	220	50	232	1,01	12	50	80	4	IP44	674	42	*				*	*	*		*		*		*	
TH 45-50/M	45	220	50	232	1,01	12	50	80	4	IP44	625	42		*			*	*	*		*		*		*	
TH 60-80	60	220	50	380	1,65	10	80	120	4	IP44	640	20								*		*		*		
TH 60-80/M	60	220	50	380	1,65	10	80	120	4	IP44	700	20		*						*		*		*		
TH 60-100	60	220	50	400	1,8	10	100	150	4	IP44	700	20								*		*		*		
TH 60-100/M	60	220	50	400	1,8	10	100	150	4	IP44	700	20		*						*		*		*		
TH 60-120	60	220	50	420	2	10	120	180	4	IP44	700	20								*		*		*		
TH 60-120/M	60	220	50	420	2	10	120	180	4	IP44	700	20		*						*		*		*		

Av. Bergamini 1545
El Palomar, Provincia de Buenos Aires , Argentina

+54 11 2071 0459
info@thesa.com.ar

THESA.COM.AR

